

PDB Horizontal Plate Clamp



Feature of PDB Horizontal Plate Clamp

1. Suitable for lifting and transport of steel plates, construction and profiled bar in horizontal position
2. Manufactured from high quality carbon steel
3. Avoid snatch or shock loading
4. The working load limit is the maximum load that the clamp are authorized to support when used in pairs with a lift angle of 60°.

In lifting operations clamps can be used in pairs or multiples.

PDB Horizontal Plate Clamp Feature

1. Suitable for lifting and transport of steel plates, construction and profiled bar in horizontal position
2. Manufactured from high quality carbon steel
3. Avoid snatch or shock loading
4. The working load limit is the maximum load that the clamp are authorized to support when used in pairs with a lift angle of 60°.

In lifting operations clamps can be used in pairs or multiples.

PDB Horizontal Plate Clamp Specification

Model	WLL(T)	Jaw opening(mm)	Weight(kg)
PDB0.80.8	0-25	2.5	
PDB1 1	0-30	3.5	
PDB1.61.6	0-30	4	
PDB2 2	0-40	5	
PDB3.23.2	0-45	6	
PDB4 4	0-50	6.5	
PDB5 5	0-55	7.5	
PDB6 6	0-65	10.5	
PDB6B 6	0-130	22	
PDB8 8	0-100	22	
PDB10 10	0-125	33	

