

Turnbuckle DIN1480

Galvanized steel turnbuckles are available with threads from M6 to M16 inclusive

According to DIN 1480, form SP-RR (2 threaded eye bolts)

Open form turnbuckle

The Turnbuckle DIN1480 is equipped with both left- and right-hand thread

Turnbuckles, also known as stretching screws or bottle screws, are used for adjusting the tension or length of ropes, cables, rods, chains and other tensioning systems in constructions, machines, fencing etc.



Feature of Turnbuckle DIN1480

Galvanized steel turnbuckles are available with threads from M6 to M16 inclusive

According to DIN 1480, form SP-RR (2 threaded eye bolts)

Open form turnbuckle

The turnbuckle is equipped with both left- and right-hand thread

Turnbuckles, also known as stretching screws or bottle screws, are used for adjusting the tension or length of ropes, cables, rods, chains and other tensioning systems in constructions, machines, fencing etc.

Specification of Turnbuckle DIN1480

Size	L1	L2	D
mm	mm	mm	mm
M5	70	34	7
M6	110	55	8
M8	110	57	11
M10	125	68	13
M11	125	68	15
M12	125	70	16
M14	140	75	18
M16	170	88	20
M20	200	105	21
M22	220	118	24
M24	255	135	26
M30	255	135	34

